

**IN THE CLAIMS:**

1. (Currently amended) Motor vehicle (1) with a roof (2), ~~which has~~ having at least one movable roof part (3) that can be fully opened, ~~that~~ and can be fully moved to achieve this full opening, ~~and that~~ wherein the movable roof part extends from an area adjacent to a windshield frame (4) to a rear, ~~especially rigid,~~ roof part (5), wherein ~~the~~ a raisable rear section of the movable roof part (3) ~~can be raised~~ is raisable in such a way that ~~the~~ a section of the movable roof part (3) ~~that is~~ located in front of the raisable rear section ~~that can be raised~~ remains in a closed position.

2. (Currently amended) Motor vehicle in accordance with Claim 1, wherein the movable roof part (3) occupies the entire width between ~~the~~ upper edges of ~~the~~ side windows (7) of the motor vehicle (1).

3. (Currently amended) Motor vehicle in accordance with Claim 1, wherein the movement of the raisable rear section into and out of its raised position is possible while the vehicle is traveling.

4. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the movable roof part (3) is covered with a flexible covering (9).

5. (Currently amended) Motor vehicle in accordance with Claim 1, wherein to allow the raisable rear section to be raised, a roof bow (27) is provided which grips beneath the rear section and is displaceably mounted on lateral frame parts (11) of the movable roof part (3).

6. (Previously presented) Motor vehicle in accordance with Claim 5, wherein at least one remotely controlled drive is provided for the displacement of the roof bow (27).

7. (Previously presented) Motor vehicle in accordance with any of Claim 1, wherein the rear roof part (5) is in the same position with the movable roof part (3) completely open and with the movable roof part (3) completely closed.

8. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) can be lowered below a belt line (31) of the automobile body.

9. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) covers a rigid roll bar (32).

10. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) is at least partially movable to create an opening for the passage of the fully movable roof part (3) to allow the latter to be opened.

11. (Previously presented) Motor vehicle in accordance with Claim 10, wherein the rear roof part (5) can be swung open about a rear axis (33) to create an opening for the passage of the roof part (3) and can be swung closed again over the opened roof part (3).

12. (Previously presented) Motor vehicle in accordance with Claim 9, wherein the opening for the passage of the movable roof part (3) is located between the rigid roll bar (32) and the opened rear roof part (5).